




SPECIFICATIONS

QUAD SERIES

MANHOLES

STANDARD FEATURES

- STEEL T-FRAME CONSTRUCTION.
- REINFORCED DIAMOND PLATE COVERS.
- 14 GAUGE SKIRTS.
- ALL STEEL COATED WITH RUST PREVENTIVE PAINT.
- SPECIALLY DESIGNED RAIN-TIGHT FRAMES AND PORTS, CAST OF DUCTILE IRON.
- NO BOLTS REQUIRED TO KEEP INNER PORTS RAIN-TIGHT.
- VARIOUS INNER ACCESS PORT ARRANGEMENTS AVAILABLE.
- OPTIONAL RETRO SPILL CONTAINERS AVAILABLE FOR 11 5/8" PORTS.
- VARIOUS RADDII AVAILABLE.
- CHANNEL-STYLE CONCRETE ANCHORS.



SECTION AA TYPICAL

QUAD ACCESS/TRIPLE PORT MANHOLES					
MODEL	A	B	C	D	E
363	35 3/4"	13 1/2"	35"	1/2"	36 1/2"
423	42"	13 1/2"	41 1/2"	1/2"	43"
483	48"	13 1/2"	46 1/2"	1/2"	49"

MODEL: QUAD ACCESS/TRIPLE PORT

QUAD ACCESS
MANHOLES
NON-WATER TIGHT

NOTE: A) SEE OPTIONAL RETRO SPILL CONTAINERS FOR SPILL CONTAINMENT OF ANY 11 5/8" PORT ON REVERSE SIDE. B) BE SURE TO SPECIFY QUANTITY OF SPILL CONTAINERS REQUIRED WHEN ORDERING.

FAIRFIELD INDUSTRIES, INC.

827 NORTH 6TH STREET NEWARK, NJ 07107


PHONE: 973-483-0100 FAX: 973-483-5333

www.fairfield-industries.com


Copyright © 2008 Fairfield Industries, Inc. All rights reserved

OPTIONAL RETROFIT SPILL CONTAINMENT FOR MULTI-ACCESS MANHOLE INNER PORTS


Optional Spill Containers can be ordered with Manholes for one or two ports as required. Four styles are available. **Note:** Add “WT” suffix to model numbers of SCM-5 Retro Series when adapting to watertight multi-access manholes.




Standard “**SCM-5 RETRO**” Spill Containers mount directly to inner ports of multi-access manholes and seal around the outside of fill riser pipes. 5 or 15 gallon capacities available.



The “**SCM-5 Retro Suffolk**” is designed and mounts the same as the standard unit except includes drain ports in spill container which alleviates overflowing onto pavement and directs overflowing into lower tank sumps.



The “**SC-5 Spill Container**” screws directly onto fill riser pipes and is independent to multi-access manholes above. Spill containers are aligned under surface ports and include a drain valve for draining spillage directly into fill riser pipe.



The “**SC-5P**” Spill Container is the same design as the SC-5 except includes a one stroke hand pump for transferring spillage back into riser pipe.