

WTL SERIES

WATERTIGHT MANHOLES

CAM-LOCK FEATURES

- CAM-LOCK BOLT DOWN DESIGN ALLOWS FOR 1/3rd TURN TO FASTEN COVERS TO FRAMES.
- CAM-LOCKS REMAIN ATTACHED TO MANHOLE COVER, NO MORE LOSING BOLTS.
- CAM-LOCKS ARE O-RING SEALED FOR BETTER WATERPROOFING.
- CAM-LOCKS ARE LOCK INDICATED AND ALLOW COVER REPLACEMENT IN ANY POSITION. NO MORE LOCATING BOLT LOCATIONS.
- CAM-LOCKS ARE OPTIONAL AND CAN BE ADDED TO ANY MANHOLE FOR WATERTIGHT OR RESTRICTED ACCESS. ADD SUFFIX "L" TO MODEL NUMBER.
- LOCK MERCHANISMS ARE CONSTRUCTED OF STAINLESS STEEL, CAST IRON AND BRASS WEAR SURFACED TO INSURE LONG TERM RELIABILITY.

STANDARD FEATURES


- REINFORCED DIAMOND PLATE STEEL COVERS WITH H-20 TRUCKLOAD RATING.
- 1/8" BUNA-N GASKET.
- 14 GUAGE SKIRTS.
- RECESSED WATERTIGHT PICKED EYE(S) FOR EASY COVER REMOVAL.
- CONCRETE CHANNEL ANCHORS.
- ALL STEEL COATED WITH RUST PREVENTIVE PAINT.
- OPTIONAL INTERNAL ACCESS PORTS AVAILABLE. SEE OUR DUAL AND TRIPLE ACCESS SERIES MANHOLES.

SOLID COVER CAM-LOCKED WATERTIGHT MANHOLES F. G MODEL A В E С D 240 WTL 24" 13" 22 1/4" 3/8" 24 3/4" 1 2 29 3/4" 28 3/4" 3/8' 30 3/4" **300 WTL** 13" 1 4 35 3/4' 35" 36 1/2" 2 4 360 WTL 13" 3/8' 38 1/2" 4 380 WTL 38' 37 1/2" 3/8' 2 13" 4 420 WTL 42" 13" 41 1/2" 1/2" 43" 2 48" 49" **480 WTL** 13" 46 1/2" 1/2" 2 6

MODEL NO: WTL

WTL WATERTIGHT SOLID COVER MANHOLES

SECTION AA



DWG NO: WTL

FAIRFIELD INDUSTRIES, INC.

4483 CHOPPEE ROAD, SC 29440 PHONE: 843-461-3894 FAX: 843-461-3907 www.fairfield-industries.com

Copyright $\ensuremath{\textcircled{O}}$ 2008 Fairfield Industries, Inc. All rights reserved

