

FEATURES:

- 3/8" THICK A36 DIAMOND PLATE COVER, NON SKID SURFACE, COVER RATED FOR H-20 WHEEL LOADING
- HEAVY DUTY T FRAME FULL WELDED CONSTRUCTION
- 1/8" BUNA GASKET
- FOUR 4 3/8-16"-18 STAINLESS STEEL HEX BOLTS
- PAINTED BLACK FINISH
- ONE (1) FLEXIBLE ENTRY FITTING (2", 3" OR 4")
- NPT CONDUIT COUPLING
- ONE (1) SINGLE STROKE PVC HAND PUMP
- 14 GAUGE 304 STAINLESS STEEL SKIRT AND BOTTOM
- FOUR (4) CHANNEL STYLE CONCRETE ANCHORS
- MADE IN USA

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FAIRFIELD IND. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FAIRFIELD IND. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED


DIMENSIONS ARE IN INCHES.
TOLERANCES ON ANGLES: $\pm 1^\circ$
FRACTIONAL: $\pm 1/16$
2-PLACE DECIMALS: ± 0.062
3-PLACE DECIMAL: ± 0.032

MATERIAL
CARBON/SST STEEL

FINISH
BLACK WET PAINT

DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	KDH	12/1/2025
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		



4483 Choppee Rd
Georgetown, SC 29440

DESCRIPTION: **SSC-18**

**SIDEWALK SPILL
CONTAINMENT**

SIZE	DWG. NO.	REV.
A	12012503-KH	0
SCALE: 1:8	WEIGHT:	SHEET 1 OF 1